









ACERO SUECO PALME S.A.P.I. de C.V. y su red de sucursales en la República

TRIPLES PARA UN BALANCE ADECUADO DE LA CARGA
CABLE CON ALMA ACERO (EIPS) OJOS CON ALGUN ACCESORIO,
DEBEN PROTEGERSE CON GUARDACABO



Diámetro de cable		TONELADAS			Eslabón maestro oblongo diámetro	
						
mm	plg				mm	pulgadas
6,35	1/4	1,70	1,40	0,97	12,70	1/2
7,94	5/16	2,60	2,10	1,50	19,05	3/4
9,53	3/8	3,70	3,00	2,20	19,05	3/4
11,11	7/16	5,00	4,01	2,90	25,40	1
12,70	1/2	6,60	5,40	3,80	25,40	1
14,30	9/16	8,30	6,80	4,80	25,40	1
15,90	5/8	10,00	8,30	5,90	31,70	1 1/4
19,05	3/4	15,00	12,00	8,40	38,10	1 1/2
22,23	7/8	20,00	16,00	11,00	38,10	1 1/2
25,40	1	26,00	21,00	15,00	44,40	1 3/4
28,60	1 1/8	31,00	26,00	18,00	50,80	2
31,75	1 1/4	38,00	31,00	22,00	57,10	2 1/4
34,93	1 3/8	46,00	38,00	27,00	69,80	2 3/4
38,10	1 1/2	55,00	45,00	32,00	69,80	2 3/4

CUADRUPLS PARA UN BALANCE ADECUADO DE LA CARGA
CABLE CON ALMA DE ACERO (EIPS) OJOS CON ALGUN ACCESORIO,
DEBEN PROTEGERSE CON GUARDACABO

Diámetro de cable		TONELADAS			Eslabón maestro oblongo diámetro	
						
mm	plg				mm	pulgadas
6,35	1/4	2,20	1,80	1,30	12,70	1/2
7,94	5/16	3,50	2,80	2,00	19,05	3/4
9,53	3/8	5,00	4,10	2,90	25,40	1
11,11	7/16	6,70	5,50	3,90	25,40	1
12,70	1/2	8,80	7,10	5,10	31,70	1 1/4
14,30	9/16	11,00	9,00	6,40	31,70	1 1/4
15,90	5/8	14,00	11,00	7,80	31,70	1 1/4
19,05	3/4	19,00	16,00	11,00	44,40	1 3/4
22,23	7/8	26,00	21,00	15,00	44,40	1 3/4
25,40	1	34,00	28,00	20,00	57,10	2 1/4
28,60	1 1/8	42,00	34,00	24,00	69,80	2 3/4
31,75	1 1/4	51,00	42,00	30,00	69,80	2 3/4
34,93	1 3/8					
38,10	1 1/2					

